ELECTRONIC WORKSHOPS IN COMPUTING

Series edited by Professor C.J. van Rijsbergen

David N. Turner (Ed)

Functional Programming, Glasgow 1995

Proceedings of the 1995 Glasgow Workshop on Functional
Programming,
Ullapool, Scotland, 10-12 July 1995

Paper:

Experiences with Clean I/O

Simon B. Jones

Published in collaboration with the
British Computer Society

©Copyright in this paper belongs to the author(s)

Experiences with Clean I/O

Simon B Jones

Department of Computing Science and Mathematics, University of Stirling

Stirling, Scotland

sbj@cs.stir.ac.uk

Abstract

The Clean system is a powerful functional programming tool. It contains experiments in a number of different areas of functional language design. In particular, it has a novel proposal for the organization of *input and output*, and contains impressive libraries of facilities for programming *graphical user interfaces*.

Clean I/O is based on collections of operations that act to cause side effects on multiple explicit abstract values representing physical I/O entities, such as files and graphical interfaces. A system of *unique types* is used to ensure that these values are individually *single threaded* through the program; and the side effecting I/O operations are therefore well controlled. This approach is distinct from monadic I/O, which is being widely adopted; monadic I/O schemes are based on a *single, implicit environment*, and guarantee that this is single threaded.

In this paper we will show that the Clean and monadic approaches to I/O merge nicely. The functionality provided by the Clean and its I/O libraries allows libraries for monadic I/O to be implemented. The paper presents an implementation of a basic I/O monad library in Clean that can serve for future development. In itself, the fact that the monadic approach can be implemented in Clean is unsurprising. However, some interesting technical difficulties arose during implementation of the monad; these and their solutions are discussed. The opportunity to express programs using the implicit environments of monadic I/O allows us to simplify Clean programs by removing some of the spaghetti, whilst retaining the generality of the explicit environments where it is the most appropriate approach.

1 Introduction

The Clean system [4, 1], recently released as version 1.0, is a powerful functional programming tool. It contains experiments in a number of different areas of functional language design. In particular, it has a novel proposal for the organization of *input and output*, and contains impressive libraries of facilities for programming *graphical user interfaces* (GUIs). A key language feature supporting the GUI programming is Clean's *uniqueness typing*. Programs operate by side effect on *multiple explicit environments*: abstract *input/output*, *file store* and individual *file* states. The uniqueness typing is required in order to ensure single threading of the states through the computation, thus guaranteeing referential transparency of programs.

In [1] Clean I/O is contrasted with other approaches, in particular the monadic approach [5, 3]. Clean I/O is distinct from monadic I/O: Clean I/O operates through *multiple explicit environments* threaded individually through a program using standard functional language constructs, whereas monadic I/O manipulates a *single, implicit environment* and provides special *combinators* for building program structures. Achten and Plasmeijer claim that Clean I/O has advantages over monadic I/O for various reasons: monadic I/O “creates a single spine of I/O operations and therefore over determines the order of evaluation”; “combining monads of different type is a rather tedious task which forms a serious practical restriction on its use”. These criticisms should certainly be taken seriously.

However, the multiple *explicit* environment approach of Clean has its own problems. It leads to code which must be expressed in terms of many different versions of the states of the environments (as they are acted upon explicitly by successive side-effecting operations), and so suffers from an explosion of primed, double primed identifiers, and so on, for the different versions. This is a form of the familiar ‘plumbing’ problem that arises with stream I/O and related approaches (for example see [2]) — and the code can resemble a ball of spaghetti that must be unravelled.

In this paper we will show that the Clean and monadic approaches to I/O merge nicely. The functionality provided by the Clean and its I/O libraries allows libraries for monadic I/O to be implemented. The paper presents an implementation of a basic I/O monad library in Clean that can serve for future development. Of course, the implementation is not as efficient as direct implementation of the monadic operations as the primitive I/O mechanism

```

OpenEvents :: !*World -> (!EVENTS, !*World);
CloseEvents :: !EVENTS !*World -> *World;

freadc :: !*File -> (!Bool,!Char,!*File);    // Read a character
fwritec :: !Char !*File -> *File            // Write a character

```

Figure 1: Some Clean library functions

(see [3]). In itself, the fact that the monadic approach can be implemented in Clean is unsurprising. However, some interesting technical difficulties arose during implementation of the monad; these and their solutions are discussed. This discussion and the monadic package are the principal contributions of this paper.

The opportunity to express programs using the implicit environments of monadic I/O allows us to simplify Clean programs by removing some of the spaghetti, whilst retaining the generality of the explicit environments where it is the most appropriate approach.

Firstly, we introduce the Clean I/O system and GUI interface briefly. Secondly, we show how typical Clean programs are constructed (using an example from the Clean 1.0 distribution, enhanced slightly). Thirdly, we show how the example could be revised if the monadic style were adopted, and we give the design of (a part of) a monadic I/O package in Clean. Fourthly, we look briefly at the interesting points and problems with Clean that arose during design of the monadic package. And finally, since the results presented here are only a partial exploration of the use of monadic structures in Clean, we look briefly at further work to be done.

2 The Clean I/O System

In this section we present the basic characteristics of the Clean I/O system, and GUI interface construction and operation.

- Programs are sub-divided into the declarative GUI specification itself (a collection of graphical interface objects, and event handler functions associated with those objects), and the main program structure that sets up the GUI.
- A `World` value encapsulates the *event stream* arising from a program's interactive environment, and the state of the system's *file store*. Event streams, file stores and individual files within the file store are *essentially unique* values: they must be used in a single threaded fashion within a program.
- The main program is a function from an initial `World` to the final `World` — which contains the residual stream of events not consumed by the program, and the final (possibly modified) file store state. Typically, a main program will open the event stream and pass it to the GUI system invoked by `StartIO`. In addition, the file store, or one or more files, may be opened and supplied to `StartIO` as part of the *user state* manipulated by the GUI.
- Library functions are provided for opening (extracting) and closing (replacing) the event stream (type `EVENTS`) and file store (type `Files`) in a `World`, and also for opening, closing and operating on individual files (type `File`) in a file store. Functions operating on opened files achieve their results by *side-effect*. Each expects to receive uniquely referenced object(s) and returns uniquely referenced object(s); further, each acts strictly, which ensures that the side-effects occur in a manifestly ordered way (the strictness annotations on their type signatures indicate this). Some examples are given in Figure 1, in which `!` indicates strictness, and `*` indicates uniqueness. Thus, `freadc` (file read character) expects a unique reference to a fully evaluated file (all previous side effects effected), and returns the same.
- A GUI system is a dynamic collection of *devices*: windows, menus, dialogues and timers. Each device has some internal state, a graphical appearance (except timers), and a collection of programmer defined *event handler functions*. The devices are encapsulated in an abstract, essentially unique `IOState`; this is created by `StartIO` from a given collection of device descriptors. Note that the `World` is distinct from the `IOState`, which needs only the event stream from the `World`. Library functions are provided that enable the event handlers to operate on the `IOState` to create, destroy, and alter the state of the individual devices. An extract of the window descriptor type and some operations are shown in Figure 2, in which `s` is the user state, `io` is an `IOState`.
- The Clean run time system manages the GUI devices: events in the environment are translated into calls of the

```

:: WindowDef *s *io
  = ScrollWindow WindowId WindowPos WindowTitle ScrollBarDef ...
  | FixedWindow WindowId WindowPos WindowTitle ... ;

OpenWindows :: ![WindowDef s (IOState s)] !(IOState s) -> IOState s ;
DrawInWindow :: !WindowId ![DrawFunction] !(IOState s) -> IOState s ;

```

Figure 2: The window descriptor type and some example operations

appropriate event handler functions. Event handlers are applied to, and must return, two unique state objects, a program specific user state, and the `IOState`; some events (for example, key presses) also provide additional argument(s) to the handler call. Each event handler application completes before the following event is handled. The event manager thus single-threads each of the states through the sequence of event handler calls. For example, an event handler specifying the action to be taken when a window is activated, deactivated or closed is of type:

```

:: WindowFunction *s *io == s -> *(io -> (s, io));

```

where `s` and `io` are as above.

Thus, in designing a Clean program, we must exercise care in the main program with the single threading of the `World`, the event stream and files, and within each event handler function with the single threading of the `IOState` and the user state. The uniqueness checking is vital in managing this.

3 Programming Clean I/O — Basic Style

We consider some program fragments based on a file to file copying demonstration program distributed with Clean 1.0; the full program is about 200 lines of Clean, including comments and white space. The program has a typical Macintosh interface: menu selections for copying and quitting, pop up file selection dialogue boxes, and a progress window for status during copying. The program fragments comprise the main program (the `Start` rule, which fires up the GUI system), and some code from within the `Copy` event handler (bound to the `Copy` menu entry in the menu descriptor). The user state is the file store (of type `Files`), and `IO` is a synonym for `IOState Files`.

The `Start` rule (Figure 3) shows the basic single threading style: The argument `world` is threaded through `OpenEvents`, `openfiles`, `closefiles` and `CloseEvents`. We see 5 incarnations of `world` (though `world3` and `world4` could be eliminated). `events` are extracted from `world`, and are then threaded through `StartIO` and are returned to the `world` in `CloseEvents`; similarly for `files`, the file store. We see 2 incarnations of `events` and of `files`.

The main action takes place in the GUI system executed *within* the call of `StartIO`, in response to the selection of “Copy” or “Quit” from the pull down menu. The event handler `Quit` signals that the GUI system should be terminated, and `StartIO` returns the final user state (the file store) and the residual event stream. The event handler `Copy` receives the user state (the file store) and the `IOState`, solicits two file names from the user (via special file selector dialogues acting through the `IOState`), and then calls `CopyFile` to perform the copy. Once partially applied to source and destination file names, `CopyFile` is precisely an event handler; it is shown in Figure 4.

`CopyFile` opens two files in the file store, creates a new progress status window, calls `CopyFiles` to do the actual copying (which acts on the individual files and the progress window), and finally closes the two files. Once again we see the single threading at work, and the multiple versions: bearing in mind that the `alerts` are `IOStates`, we have 8 incarnations of `io`, 5 incarnations of `files`, 3 incarnations of the source file `sfile`, and 2 incarnations of the destination file `dfile`. Particularly irritating is that when we look up the length of `sfile` we obtain a ‘new version’ of `sfile`; this is necessary to guarantee single threading of the essentially unique file object, and also fixes the point in the computation that we look up the length, but the need to consider a new identifier is rather a diversion.

In the next section we will show how to reorganize the `Start` rule using the monadic style.

```

Start :: *World -> *World;
Start world = world4;
  where {
    (events,world1 ) = OpenEvents world;
    (files ,world2) = openfiles world1;
    (files',events')
      = StartIO [MenuSystem [menu], WindowSystem [progresswindow]]
              files [] events;
    world3 = closefiles files' world2;
    world4 = CloseEvents events' world3;
    menu = PullDownMenu 1 "Copy" Able
          [MenuItem 1 "Copy..." (Key 'C') Able Copy,
           MenuItem 2 "Quit"      (Key 'Q') Able Quit];
    progresswindow = FixedWindow 1 ProgressWindowPos "Copy"
                        ProgressInitWindowDomain
                        (MkUpdateFn (CopyOrQuit "File copy")) [];
  };

```

Figure 3: File copying program Start rule

```

CopyFile :: String String Files IO -> (Files,IO);
CopyFile source dest files io
  | not sopen = (files1,alert1);
  | not dopen = (files2,alert2);
  | io_error = (files5,alert3);
  | not dclose = (files5,alert4);
  | not sclose = (files5,alert5);
= (files5,io2);
  where {
    (sopen,sfile,files1) = fopen source FReadData files;
    (dopen,dfile,files2) = fopen dest FWriteText files1;
    (files3,io1)         = SetProgressWindow source dest files2 io;
    (length,sfile')      = FileLength sfile;
    (io_error,sfile'',dfile',io2)
      = CopyFiles 0 (inc length) sfile' dfile' io1;
    (dclose,files4)      = fclose dfile' files3;
    (sclose,files5)      = fclose sfile'' files4;
    alert1 = Alert ["Source file could not be opened."] io;
    alert2 = Alert ["Destination file could not be opened."] io;
    alert3 = Alert ["An I/O error occurred during copying."] io2;
    alert4 = Alert ["Destination file could not be closed."] io2;
    alert5 = Alert ["Source file could not be closed."] io2;
  };

```

Figure 4: File copying event handler

4 Programming Clean I/O — Monadic Style

We consider the `Start` rule: here we need to manipulate a monad encapsulating an implicit state comprising the `World`, and the event stream extracted from it. We plan to import types and operations from a reasonably standard monadic package, the `WorldMonad`. The state definition is given below, and the full definition of `WorldMonad` is given in Appendix A; some of the details are discussed in the next section.

The implicit state manipulated by the monad is a record:

```
:: *WorldState = { theWorld :: *World,
                  eventStream :: *EVENTS, eventsOpen :: Bool,
                  filesOpen :: Bool
                  };
```

The `*` decorating `WorldState` indicates that it is essentially unique: the uniqueness attribute is implicit in all occurrences of the type `WorldState`. The two state flags `eventsOpen` and `filesOpen` allow the monad operations to reject multiple attempts to extract the event stream and file store from `theWorld`.

`Action_W x` is the type of actions in the `World` monad, returning a value of type `x`.

```
:: Action_W x ::= !WorldState -> (x, !WorldState)
```

The strictness annotations on `WorldState` in `Action_W` are not (strictly) necessary, but are conceptually tidy. The following monad operations are provided:

`Run_W` gets us into the monad, executing an `Action_W` on a given world, and returning a pair comprising the action's result and the final world (hence the `snd` in the new `Start` rule below).

`Then_W`, `Bind_W` These are the standard “action followed by action”, with `Bind_W` passing the result from the first action as argument to the second.

The remaining operations correspond to the Clean I/O library functions used in the original `Start` rule, but now in the `World` monad setting:

`OpenEvents_W`, `CloseEvents_W` These are responsible for extracting the event stream from, and reinstalling it in, `theWorld`. They return `Void` results.

`GetFiles_W`, `PutFiles_W` These are responsible for extracting the file store from `theWorld` and *vice versa*. Since the file store is not held in the `WorldState`, `GetFiles_W` returns the file store as its result, and `PutFiles_W` expects it as its argument.

`StartIO_W` This creates the specified GUI system, supplies it with the event stream from the `WorldState`, replacing it with the resultant residual stream and returning the final user state as the action's result.

We can now rewrite the `Start` rule, as shown in Figure 5.

We would argue that the operational structure of this code is clearer than the original `Start` rule: there is less text, there are fewer additional identifiers, and the reader does not have to trace the interdependence of a collection of where definitions in order to deduce the order of events.

A similar technique could be applied to `CopyFile`, though it is more tricky as there are two files as well as the `IOState` and the file store to be threaded, and it is not clear whether threading them as a compound state is the appropriate solution. A more complex solution may be appropriate in general. Designing a monad for use *within* event handlers, and reorganizing `CopyFile` is on-going work. `WorldMonad` is not appropriate in this context, as event handlers are not concerned with the `World`, but instead with the user state and `IOState`.

```

Start :: *World -> *World;
Start world = snd(Run_W CopyProgram world);

CopyProgram :: Action_W Void;
CopyProgram = OpenEvents_W Then_W
  GetFiles_W Bind_W (\files ->
    StartIO_W [MenuSystem [menu],
      WindowSystem [progresswindow]] files [])
  Bind_W (\files ->
    PutFiles_W files Then_W
    CloseEvents_W );
  where {
    menu = PullDownMenu 1 "Copy" Able
      [MenuItem 1 "Copy..." (Key 'C') Able Copy,
       MenuItem 2 "Quit"      (Key 'Q') Able Quit];
    progresswindow = FixedWindow 1 ProgressWindowPos "Copy"
      ProgressInitWindowDomain
      (MkUpdateFn (CopyOrQuit "File copy")) [];
  };

```

Figure 5: Revised Start rule, using World monad

5 Discussion: Design Issues and Problems

The reader should refer to the full module definition in Appendix A.

5.1 Design Issues

As designed, the World monad copes well with restructuring the Start rule of the file copying program.

However, some design decision have been made that perhaps will need reviewing. Specifically, these concern the contents of the WorldState. This necessarily contains the World. It also contains the event stream extracted from it by OpenEvents_W and a boolean flag to indicate that the stream has been extracted. Although the WorldState contains a flag indicating that the file store has been extracted from the World, the file store itself is *not* held in the WorldState; GetFiles_W extracts the file store from the World, and returns it directly as its action result.

The rationale for this asymmetric treatment is as follows:

- In the Clean I/O scheme, operations on the event stream are very limited: the stream may be opened and closed and handed to StartIO. Therefore it is retained in the WorldState as the program has no need to manipulate it explicitly, and StartIO_W then knows exactly where to find it. It could be argued that there is no need for explicit operations OpenEvents_W and CloseEvents_W as StartIO_W could do them implicitly — this would, of course, introduce even more asymmetry into the event stream and file store treatment.
- On the other hand, most GUI-oriented programs need to remove the file store completely from the WorldState simply in order to build it into a program-specific state for use by the GUI system. Thus even if operations were provided to move the file store in and out of the World *within* the WorldState (similar to OpenEvents_W and CloseEvents_W), they would be of limited use, and operations allowing the program to manipulate the file store explicitly (like GetFiles_W and PutFiles_W) would still be needed. If programs needed significant file access *outside* their GUI component, then there would be reason to adopt the latter strategy mentioned above.

Unfortunately the WorldMonad will probably be of no use in restructuring the CopyFile event handler, as it does not depend on the World, nor explicitly on the event stream. For GUI event handlers, a monad encapsulating the GUI system state and a customizable user state is probably what is required. It is in handlers like CopyFile that the greatest flexibility is required, and it is here that we are likely to encounter the greatest tension between the basic Clean and monadic approaches: either all state components remain in the monadic state (the file store, files, etc, much

like Haskell 1.3 monadic I/O), possibly leading to an over-cumbersome state and over-sequentialization of the code, or some are extracted and explicitly ‘plumbed’ through the handler. The design decisions here are likely to be quite tricky, and currently remain as future work.

5.2 Implementation Problems

A number of interesting subtleties in the use of Clean 1.0, especially the type system, arose in implementing the `WorldMonad` module; solving them provided valuable lessons. Their solution introduced some apparent peculiarities in the form of the code, and exposed some possible problems with (the current release of) Clean itself.

- The form of many equations is a little unexpected. For example:

```
(Then_W) infixr :: (Action_W Void) (Action_W .y) -> Action_W .y;
(Then_W) a1 a2 = \world_st -> a2 (snd (a1 world_st));
```

where we might expect to see

```
(Then_W) a1 a2 world_st = a2 (snd (a1 world_st));
```

The explicitly curried `\world_st` form is necessary as Clean verifies the ‘explicit’ arity of the type given in the type signature against the actual number of arguments in the equation (rewrite rule) — in this case it is 2 (rather than 3, which might be expected since `Action_W .y` is function type). Note that this does *not* restrict the way in which the function is called.

[Aside: As a bonus, the `\world_st` form enables the Clean code generator to optimize the tail call of `a2`. Without this the stack usage would, in general, be unbounded — a problem that bedevilled early tests of the `WorldMonad` code in which functions were not explicitly typed, and `Then_W` was in the second form above. This is a subtle interaction between type checking, higher order functions and boxed and unboxed function results: in the first form of `Then_W`, un-boxing code needs to be inserted after the call of `a2`, and thus that call is *not* in a tail call position. It is a not entirely satisfactory situation.]

- The types of the functions `Run_W`, `Then_W`, `Bind_W` and `Discard_W` have *dot annotations* on the type variables. The best example is:

```
(Bind_W) infixr :: (Action_W .x)(.x->(Action_W .y))->Action_W .y;
```

This is a simple form of uniqueness polymorphism: it means that `x` can be uniformly instantiated with a unique type or a non-unique (i.e. ‘not necessarily unique’) type, and similarly `y`. If the dots were absent, then the types would be non-unique, and although such a function could be applied to a unique argument (since unique is coercible to non-unique in this case), it could not guarantee a correspondingly unique result. Thus, in general, if the monad operations are to be used to single thread essentially unique values, the dots are required on `x` and `y`. In themselves, the functions would satisfy the uniqueness check without the dots, but then some *applications* of them would not be valid.

For example, in the file copying program, the fragment

```
GetFiles_W Bind_W (\files ->
StartIO_W ... files ... )
```

requires that the type variable `x` in `Bind_W` be dotted, as the file store (the result of `GetFiles_W`) is essentially unique.

- The uniqueness polymorphism problem arises in a harder form in `Unit_W`, which must have the type:

```
Unit_W :: v:x -> v:Action_W v:x;
```

For the reasons in the previous point, the type variable `x` must at least be dotted. However, in this case it is not enough: the function's type specification itself will not satisfy the uniqueness check. The reason is that `Unit_W` may be partially applied to an essentially unique value (remember that `Action_W x` is a function type); the closure formed must preserve the uniqueness of the value now embedded within it, i.e. the *closure itself* must not become multiply referenced. Therefore, the `Action_W x` must be treated as *at least as unique* as `x`. This is specified by annotating `x` with a *uniqueness variable* `v`, and also using this for the `Action_W`.

Thus, if `Unit_W` is applied to a non-unique `x`, the `Action_W` closure will be non-unique, whereas if it is applied to a unique `x`, the `Action_W` closure will be unique and may only be used in a unique context.

There is an additional uniqueness `*` in the type of `PutFiles_W` for a similar reason: `Files` is essentially unique (see Figure 6).

- A `WorldState` is a record. Each of the `World` monad operations is applied to a unique `WorldState` and returns a `WorldState` differing from its argument in one or more fields. Clean contains a special record construction syntax for such record “updating” (and, if uniqueness checks are satisfied, code can be generated to destructively update the record — although the compiler currently does not do this). Figure 6 shows how this may be used neatly in `PutFiles_W`.

```
PutFiles_W :: Files -> *Action_W Void;
PutFiles_W files
  = \world_st ->
    if world_st.filesOpen
      (Void_val, {world_st &
                  theWorld = closefiles files world_st.theWorld,
                  filesOpen = False})
      (abort "Abort PutFiles_W: Files not open");
```

Figure 6: `PutFiles_W` expressed as a record update

However, the uniqueness checker is currently not flexible enough to accept *all* the operations in the module expressed this way — it is sometimes unable to detect that the essentially unique field values *are* being used in a single threaded way. For consistency of presentation, the record update syntax is ignored here.

6 Summary and Further Work

We have shown how the features of Clean 1.0 and its I/O libraries lead to a basic style of program construction in which one deals with a multiplicity of versions of abstract I/O object states; a good deal of ‘plumbing’ has to be unravelled in order to understand large segments of code. In order to alleviate this problem we have explored how a monadic approach can be adopted to simplify the non-GUI aspects of program construction.

A complete ‘World’ monad module is given, and some of the design decisions are discussed: for the application given, which is typical in many ways, the given `WorldMonad` works well, but it may be argued that a different choice of system and I/O objects should be in the implicit state threaded by the monad. The `World` monad is still being developed.

A number of interesting subtleties in the use of Clean 1.0, especially the type system, were exposed in implementing the `WorldMonad` module. When dealing extensively with uniquely typed objects, if the type signatures of functions are to be given (as they must be if they are to be exported from a module), and are to be as precise as possible, then they may require annotating with uniqueness information in a way that is not immediately obvious before being acceptable to the type checker.

Within Clean GUI system event handler functions the problem is harder. It is here that we are likely to encounter the greatest tension between the basic Clean and monadic approaches: flexible, explicit ‘plumbing’ versus an all-inclusive monadic state. The best way forward is not clear, and is likely to be a careful hybrid approach. The design decisions

here are likely to be quite tricky, and this is the main area for further work. The investigation of a monadic approach for the event handler functions promises to expose more of the different approaches' strengths and weaknesses.

7 References

- [1] Peter Achten and Rinus Plasmeijer. The ins and outs of Clean I/O. *Journal of Functional Programming*, 5:81–110, 1995.
- [2] Simon B Jones and Andrew F Sinclair. Functional programming and operating systems. *The Computer Journal*, 32(2):162–174, April 1989.
- [3] Simon Peyton Jones and Philip Wadler. Imperative functional programming. In *Proceedings of the 20th ACM SIGACT-SIGPLAN Symposium on the Principles of Programming Languages*, pages 71–84. ACM, January 1993.
- [4] Rinus Plasmeijer and Marko van Eekelen. *Functional Programming and Parallel Graph Rewriting*. Addison-Wesley, 1993.
- [5] Philip Wadler. The essence of functional programming. In *Proceedings of the 19th Annual Symposium on Principles of Programming Languages*, January 1992.

A WorldMonad.icl

(The definition module WorldMonad.dcl is omitted. All functions are exported, and Action_W x is exported as an abstract type. WorldState, Void_val and EmptyWorldState are private.)

```
implementation module WorldMonad;

import StdEnv, deltaEventIO, deltaIOSystem;

:: *WorldState = { theWorld :: *World,
                  eventStream :: *EVENTS, eventsOpen :: Bool,
                  filesOpen :: Bool
                  };
:: Action_W x ::= !WorldState -> (x, !WorldState);
    // The World monad implementing type

Void_val :: Void;
Void_val = abort "Attempt to access void world monad result";

EmptyWorldState :: WorldState;
EmptyWorldState = { theWorld = abort "Abort: No world available",
                  eventStream = abort "Abort: Events not open",
                  eventsOpen = False,
                  filesOpen = False };

Run_W :: (Action_W .x) !*World -> (.x, !*World);
Run_W program world = (x, world')
  where {
    (x, {theWorld = world'}) = program {EmptyWorldState &
                                         theWorld = world }; };

Done_W :: Action_W Void;
Done_W = \world_st -> (Void_val, world_st);

Unit_W :: v:x -> v:Action_W v:x;
```

```

Unit_W x = \world_st -> (x, world_st);

(Then_W) infixr :: (Action_W Void) (Action_W .y) -> Action_W .y;
(Then_W) a1 a2 = \world_st -> a2 (snd (a1 world_st));

(Bind_W) infixr :: (Action_W .x)(.x->(Action_W .y))->Action_W .y;
(Bind_W) a1 a2 = \world_st -> case a1 world_st of
    { (x, world_st') -> a2 x world_st'; };

(Discard_W) infixr :: (Action_W .x) (Action_W .y) -> Action_W .y;
(Discard_W) a1 a2 = \world_st -> a2 (snd (a1 world_st));

OpenEvents_W :: Action_W Void;
OpenEvents_W
    = \{theWorld,eventStream,eventsOpen,filesOpen} ->
        if eventsOpen
            (abort "Abort OpenEvents_W: Event stream already open")
            (case OpenEvents theWorld of
                { (events,world')
                    -> (Void_val, {theWorld = world',
                                   eventStream = events,
                                   eventsOpen = True,
                                   filesOpen = filesOpen}); });

CloseEvents_W :: Action_W Void;
CloseEvents_W
    = \{theWorld,eventStream,eventsOpen,filesOpen} ->
        if eventsOpen
            (Void_val, {theWorld = CloseEvents eventStream theWorld,
                        eventStream = abort "Abort: Events not open",
                        eventsOpen = False,
                        filesOpen = filesOpen})
            (abort "Abort CloseEvents_W: Events not open");

GetFiles_W :: Action_W Files;
GetFiles_W
    = \{theWorld,eventStream,eventsOpen,filesOpen} ->
        if filesOpen
            (abort "Abort GetFiles_W: Files already open")
            (case openfiles theWorld of
                { (files,world')
                    -> (files, {theWorld = world',
                                   eventStream = eventStream,
                                   eventsOpen = eventsOpen,
                                   filesOpen = True}); });

PutFiles_W :: Files -> *Action_W Void;
PutFiles_W files
    = \{theWorld,eventStream,eventsOpen,filesOpen} ->
        if filesOpen
            (Void_val, {theWorld = closefiles files theWorld,
                        eventStream = eventStream,
                        eventsOpen = eventsOpen,
                        filesOpen = False})
            (abort "Abort PutFiles_W: Files not open");

```

```

StartIO_W :: !(IOSystem *s (IOState *s)) !*s !(InitialIO *s)
                                     -> *Action_W !*s;

StartIO_W iosystem initprogstate initialio
  = \{theWorld,eventStream,eventsOpen,filesOpen} ->
    if eventsOpen
      (case StartIO iosystem initprogstate initialio eventStream of
        { (finalstate, eventStream`)
          -> (finalstate, {theWorld = theWorld,
                        eventStream = eventStream`,
                        eventsOpen = eventsOpen,
                        filesOpen = filesOpen}); })
      (abort "Abort StartIO_W: Events not open");

```